

Dispozitiv de testare

Testing Devices

S3600/ 1 (CPR)

Pentru curatarea si controlul ratei de curgere, si in cele din urma testarea curgerii sistemului de racire a matritelor in afara masinii de injectie.

For the cleaning, controlling of flow rate and finally leakage testing of mould cooling systems outside of the injection moulding machine.

Caracteristici:

- Capacitate rezervor: 30 Litri (Apa cu min. 50% glicol)
- Pompa cu motor electric
- Preselectarea presiunii de setare
- Controlul debitului (debitmetru)
- Filtrare dubla a lichidului cu indicatie vizuala a conditiei de filtru
- Dispozitiv de curatare cu jet de aer pentru pasaje

Features:

- Tank capacity: 30 litres (water with min. 50% glycol agent)
- Electric motor pump
- Preselection of pressure setting
- Flow control (flow meter)
- Double filtering of the liquid with visual indication of filter conditions
- Air jet cleaning device for the passages

Nr. / No.
S3600/ 1



S3602/ 1 (CPC)

Pentru instalarea etansa a cilindrilor hidraulici

For the leakproof installation of hydraulic cylinders

Caracteristici:

- Capacitate rezervor: 40 Litri
- Debit: 4 – 15 l/min
- Presiunea 50 – 200 bar

Features:

- Tank capacity: 40 litres
- Flow rate 4 – 15 litres / min
- Pressure 50 – 200 bar

Nr. / No.
S3602/ 1

